

<b>RILEY</b>														
Model	WLL at 0°Vertica		A Jaw grip Adjustment		H Jaw Aperture		J Inside Shackle Crown to Spacer		B Inside Shackle Wid		K Sideplate Thickness	Average Weight		
	Lbs	kg	Inch( min-m	mm(min-ma	inch	mm	inch	mm	inch	mm		mm	Lbs	kg
	S2A	6720	3048	3"-7 1/2"	76-190	7/8"	22	3 3/4"	95	n/a		n/a	12.5	16.3
S2AX	6720	3048	5"-13 3/4"	127-350	7/8"	22	3 3/4"	95	n/a	n/a	12.5	32	11.5	
S3A	11200	5080	6"-12"	150-305	1 5/8"	32	4 1/8"	105	n/a	n/a	12.5	32.8	15	
S4S	13440	6096	8"-18"	203-457	1 5/8"	42	4 1/8"	105	n/a	n/a	12.5	41.5	18.8	
S4A	22400	10160	8"-18"	203-457	1 1/2"	42	5 1/8"	130	n/a	n/a	20	60.2	27.3	
S12	33601	15241	8"-18"	203-457	2"	50	5 7/8"	150	n/a	n/a	20	118.4	49.5	
S14	33601	15241	16"-24"	406-610	2 1/2"	63	5 7/8"	150	n/a	n/a	20	138.8	58.5	
S15	44800	20320	8"-18"	203-457	2"	51	8 1/4"	210	4 1/2"	114	12.5	139.1	65.5	

<b>RILEY</b>														
Model	WLL		A Adjustment		B To accommodate Beam Flange Thickness		C Headroom		D Max. Hook Size		E Max. Web Thickne		Average Weight	
	Lbs	kg	inch min-ma	mm min-ma	inch	mm	inch	mm	inch	mm	inch	mm	Lbs	kg
USC5	11200	5080	5"-12"	125-305	1"	25.4	5 3/4"	146	2 3/4"	70	1 1/4"	32	60	28.5